

COMMUNICATION DEVICE FOR SELECTING ROUTE OF PACKET

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a communication device for selecting a route of a packet in a packet switching network comprising an IP (Internet Protocol) network such as the Internet, intranets etc.

2. Description of the Related Art

10 The Internet is a data network in which the terminals are mutually connected worldwide. The Internet users rapidly increase. What is characteristic of the Internet is that routing is executed based on an IP datagram (IP packet) as an unit, and a connection is not set at an IP level.

15 In the Internet, the IP packets are forwarded by reference to a routing table in which to describe a destination address and a next hop (router) corresponding to the destination address. The destination address contains a piece of address mask information in order to make searchable a network unit of the
20 destination or a predetermined aggregated unit.

 In general, means for creating the routing table involves the use of a dynamic routing protocol such as RIP (Routing Information Protocol), OSPF (Open Shortest Path First) and so on. Main objects of the use of dynamic routing are to automate
25 designing of routes of packets and to dynamically react to extension and failure of nodes and links. Dynamic routing aims at creating a routing table. The routing table based on dynamic

routing is created in a way that a distributed algorithm resolves such a spanning tree as to minimize a router's cost (Metric) in the network. RIP and OSPF account for a hop count (the number of routers to the destination) as a cost needed for
5 creating the routing table but do not account for a network's load etc as a cost.

On the other hand, there is used a method by which an operator (e.g., a network administrator) manually writes entries to the routing table. This method is known as static
10 routing in contrast with dynamic routing.

According to dynamic routing, the cost is recalculated corresponding to a change in topology of the network due to extension or failure of the nodes and the links, and the routing table is automatically updated corresponding to a result of the
15 recalculation.

By contrast, according to static routing, even if the topology changes, the contents of the routing table are not changed as far as the operator does not update the routing table. Therefore, according to static routing, the operator must
20 update the routing table when the topology changes. So far as the operator does not acknowledge, the contents of the routing table are not changed. Hence, intentional control of the operator (which is called a "policy") can be reflected in the network.

25 According to dynamic routing, even when there exist a plurality of routes from a certain network to other network, the spanning tree is that there is only one route for minimizing

the hop count. Namely, only one route for minimizing the hop count is selected (by a spanning tree algorithm) among the plurality of routes.

An allowable capacity of route (load to the network) has
5 hitherto not been considered for selecting the route.
Therefore, if traffic exceeding the allowable capacity of the selected route occur, packets of the traffic over the allowable capacity are discarded.

A main stream in the Internet may be served for providing
10 only connectivity (reachability of the packet). Only the reachability of IP packet to a destination of the communication is secured by endorsing the connectivity.

On the other hand, what has been required over the recent years may be services for guaranteeing predetermined
15 communication qualities such as data communication services for securing, VoIP (Voice over IP: IP network based voice communications), and a video transfer and so on. Some sort of policy must be reflected in the network in order to actualize the services for guaranteeing the communication qualities.

20 Herein, if static routing is adopted, the predetermined policy can be reflected in the network. According to static routing, however, the operator must update the routing table. Static routing is therefore incapable of quickly troubleshooting failure in the network.

25

SUMMARY OF THE INVENTION

It is a primary object of the present invention to provide

a communication device capable of reflecting a policy if failure do not occur in a route, and securing reachability of packets even if the failure occur in the route.

To accomplish the above object, according to one aspect
5 of the present invention, a communication device for selecting a route of a packet comprises a static routing table storing first routing information of the packet based on static routing; a dynamic routing table storing second routing information of a packets obtained based on a dynamic routing protocol; and
10 a judging unit obtaining the first and second routing information corresponding to a packet are obtained from the static routing table and the dynamic routing table; if failure do not occur in a static route as a route corresponding to the first routing information, selecting the static route as a route
15 to which the packet should be forwarded; and selecting, if the failure occur in the static route, a dynamic route as a route corresponding to the second routing information obtained from the dynamic routing table, instead of the static route.

According to the present invention, if the failure do not
20 occur in the static route corresponding to the first routing information obtained from the static routing table, the static route is selected as the route to which the packet should be forwarded. Whereas if the failure occur in the static route, the dynamic route corresponding to the second routing
25 information obtained from the dynamic routing table, is selected.

With this contrivance, if no failure (fault) occur in the

static route (normal time), the packet is forwarded to the static route, thereby a policy is reflected. If the failure (fault) occur in the static route, the packet is forwarded to the dynamic route, whereby the reachability of the packets can
5 be secured.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing construction of an inputted packet processor in a first embodiment;

10 FIG. 2 is a diagram showing construction of the inputted packet processor in a second embodiment;

FIG. 3 is a diagram showing construction of the inputted packet processor in a third embodiment;

15 FIG. 4 is a diagram showing construction of the inputted packet processor in a fourth embodiment;

FIG. 5 is a diagram showing construction of the inputted packet processor in a fifth embodiment;

FIG. 6 is a diagram showing construction of the inputted packet processor in a sixth embodiment;

20 FIG. 7 is a diagram showing construction of the inputted packet processor in a seventh embodiment;

FIG. 8 is an explanatory diagram showing a format of an IPv4 header;

25 FIG. 9 is a diagram showing construction of the inputted packet processor in an eighth embodiment;

FIG. 10 is an explanatory diagram showing a format of an IPv6 header;

FIG. 11 is a diagram showing construction of the inputted packet processor in a ninth embodiment;

FIG. 12 is an explanatory diagram showing a format of a MPLS shim header;

5 FIG. 13 is a diagram showing construction of the inputted packet processor in a tenth embodiment;

FIG. 14 is a diagram showing construction of the inputted packet processor in an eleventh embodiment;

10 FIG. 15 is a diagram showing construction of the inputted packet processor in a twelfth embodiment;

FIG. 16 is a diagram showing construction of the inputted packet processor in a thirteenth embodiment;

FIG. 17 is an explanatory diagram showing a format of an ST (ST2) header;

15 FIG. 18 is a diagram showing construction of the inputted packet processor in a fourteenth embodiment;

FIG. 19 is a diagram showing construction of the inputted packet processor in a fifteenth embodiment;

20 FIG. 20 is a diagram showing construction of the inputted packet processor in a sixteenth embodiment;

FIG. 21 is a diagram showing construction of the inputted packet processor in a seventeenth embodiment;

FIG. 22 is a diagram showing construction of the inputted packet processor in a eighteenth embodiment;

25 FIG. 23 is a diagram showing construction of the inputted packet processor in a nineteenth embodiment;

FIG. 24 is a diagram showing construction of the inputted

packet processor in a twentieth embodiment;

FIG. 25 is a diagram showing construction of the inputted packet processor in a twenty first embodiment;

FIG. 26 is a diagram showing construction of a
5 communication device in the embodiment;

FIG. 27 is a diagram showing an example of communications using the communication device in the embodiment;

FIG. 27 is a diagram showing an example of communications using the communication device in the embodiment;

10 FIG. 28 is a diagram showing an example of the communications using the communication device in the embodiment;

FIG. 29 is a diagram showing an example of the communications using the communication device in the
15 embodiment; and

FIG. 30 is a diagram showing an example of the communications using the communication device in the embodiment.

20 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will hereinafter be described with reference to the accompanying drawings.

[First Embodiment]

To start with, a communication device in a first
25 embodiment of the present invention will be explained.

[Construction]

FIG. 26 is a diagram showing construction of a

communication device T. the present invention is applied in the form of the communication device T to, for example, a router (gateway) and a label switch such as a layer 3 switch, MPLS (Multi Protocol Label Switching) etc.

5 Referring to FIG. 26, the communication device T includes a switch 5 and a plurality (n-pieces) of packet processing units U (U1, U2, U3,, Un). Each of the packet processing units U has a line interface unit Z, an inputted packet processor (inputted packet processing unit) 1 and an outputted packet processor (outputted packet processing unit) 1a, which are
10 respectively connected to the switch 5.

Each of the line interface unit Z (Z1, Z2, Z3, ..., Zn) is an interface connected to other communication device through a communication line and corresponding the standard of a
15 communication line serving as a packet transmission path. In an example shown in FIG. 26, the line interface unit Z1 accommodates a SONET (Synchronous Optical Network) circuit. The line interface unit Z2 accommodates a WDM (Wavelength Division Multiplexing) circuit. The line interface unit Z3
20 accommodates an ATM (Asynchronous Transfer Mode) circuit. The line interface unit Zn accommodates an Ethernet circuit.

Each line interface unit Z converts a packet forwarded via the communication line into a format in which the packet can be processed by the inputted packet processor 1, and inputs
25 the thus converted packet to the inputted packet processor 1. On the other hand, each line interface unit Z converts the packet inputted from the outputted packet processor 1a into a format

in which the packet can be forwarded to the communication line accommodated in the interface unit Z itself, and forwards the converted packet to the communication line.

Each inputted packet processor 1 determines a route (next hop) via which the packet inputted from the corresponding line interface unit Z should be forwarded, and inputs the packet to the switch 5. Each outputted packet processor 1a executes a necessary process on the packet inputted from the switch 5, and thereafter inputs the packet to the line interface unit Z.

FIG. 1 is a diagram showing construction of the inputted packet processor 1 shown in FIG. 26. Referring to FIG. 1, the inputted packet processor 1 comprises a static routing table 2, a dynamic routing table 3 and a judgement processing unit (corresponding to a judging unit) 4.

The static routing table 2 is a routing table created based on static routing. The static routing table 2 contains pieces of next hop information (corresponding to first routing information of a packet), for guiding a packet 6 to its destination, written by an operator (network administrator) of the communication device T. The next hop information is set so that a policy of guaranty etc of a communication quality such as QoS (Quality of Service) reflects in the network.

The dynamic routing table 3 is a routing table created based on dynamic routing. The dynamic routing table 3 is created according to a routing protocol such as RIP, OSPF etc. The dynamic routing table 3 contains next hop information (corresponding to second routing information of a packet)

corresponding to destination information (which corresponds to a common search key) of the packet 6.

The next hop information retained (stored) in the dynamic routing table 3 is updated so that a cost of a route relating
5 to the destination of the packet 6 is minimized according to a change in terms of topology of the network to which the communication device T is connected.

The switch 5 forwards the inputted packet to a packet processing unit Y accommodating a link corresponding to the next
10 hop information. With this routing, the switch 5 is in principle in such a state that links for connecting the communication device T to other communication devices are established. Referring again to FIG. 1, the switch 5 establishes a link (route) A specified in the static routing
15 table 1, and a link (route) B specified in the dynamic routing table 2.

The judgement processing unit 4 selects which table, the static routing table 2 or the dynamic routing table 3, is to be used on the basis of failure (fault) information detected
20 or under the control of the operator of the communication device T. To be more specific, the judgement processing unit 4, if no failure occur in the link (route) A, selects the next hop information from the static routing table 2. By contrast, the judgement processing unit 4, if a failure occur in the link
25 (route) A, selects the next hop information from the dynamic routing table 3.

The judgement processing unit 4, if the failure is

discovered by a fault detecting unit incorporated into each link or by an existing technology such as connection monitoring of PPP (Point-to-Point Protocol), receives a signal indicating this failure. Further, the judgement processing unit 4
5 receives a signal relative to an selective indication given from the operator.

Note that the judgement processing unit 4 may make a judgement as to failure of any one link in the communication device T, and may also make a judgement as to the packets that
10 should be transferred to the link having failure. In the latter case, the judgement processing unit 4 is notified of data about a hop (router) in which the fault occur, and the judgement can be made by comparing this piece of fault hop information with the next hop information taken out of the routing table.

15 Further, if the failure occur in any one of a plurality of links existing a static route between the communication device T and a destination of the packet, the judgement processing unit 4 may select the next hop information from the dynamic routing table 3.

20 The inputted packet processor 1 (the static routing table 2, the dynamic routing table 3 and the judgement processing unit 4) may be actualized by either hardware or software. It is, however, preferable in terms of gaining a faster processing speed than by software that the inputted packet processor 1 is
25 configured by hardware (e.g., ASIC (Application Specific Integrated Circuit)).

<Function>

Functions of the inputted packet processor 1 will be explained. Referring to FIG. 1, when the inputted packet processor 1 receives the packet 6, destination information of the packet 6 as a search key contained in the packet 6 are
5 respectively inputted to the routing tables 2 and 3. On the other hand, the packet 6 itself is inputted to the switch 5.

The static routing table 2 inputs the next hop information (the information of the link (route) A) corresponding to the inputted destination information of the packet 6 to the
10 judgement control unit 4. Further, the dynamic routing table 3 inputs, to the judgement control unit 4, the next hop information (the information of the link B) corresponding to the inputted destination information of the packet 6.

The judgement processing unit 4, when receiving the next
15 hop information from the static routing table 2 and the dynamic routing table 3, judges whether the failure information of the link A is being inputted or has been inputted to the judgement processing unit 4 itself.

At this time, the judgement processing unit 4, when not
20 receiving the failure information, inputs the next hop information received from the static routing table 2 to the switch 5. Whereas if receiving the failure information, the judgement processing unit 4 inputs the next hop information received from the dynamic routing table 3 to the switch 5.

25 The switch 5, based on the next hop information received from the judgement processing unit 4, forwards the inputted packet 6 to one of the links A and B. That is, the switch 5,

when receiving the next hop information in the static routing table 2, forwards the packet 6 to the link A. In contrast with this, the switch 5, when receiving the next hop information in the dynamic routing table 3, forwards the packet 6 to the link

5 B.

Thus, in the inputted packet processor 1, when it can be transferred the packet 6 to a certain destination by use of any one of the links A and B, if no failure occur in the link (route) A, the link A is priority selected as a route to the destination.

10 On the other hand, if failure occur in the link A, the link (route) B is selected as a route to the destination.

<Operation>

In accordance with the first embodiment, when the predetermined communication services (for example, VoIP, transferring of video (movie) information, and data

15 communication services for guaranteeing capability of the services), the communication device T guarantees the communication quality such as QoS (Quality of Service) by preparing the route (link A) set by static routing added with

20 QoS. If the failure occur on the route (link A) specified by static routing, the route (link B) created by dynamic routing is selected. Thereby reachability of packets can be secured even if unable to guarantee an agreed QoS, when the failure occur. Thereby, each of the inputted packet processor in the

25 embodiments functions as a first route selecting unit and a second route selecting unit.

Referring to FIG. 27, a network is configured by

connecting a plurality of routers R1 - R5 corresponding to the communication devices T to each other via communication lines. A host (terminal device) X is connected to the router R1, and a host (terminal device) Y is connected to the router R5.

5 The static routing table 2 held by the router R1 is stored with link information relating to a line number "a" (which will hereinafter be referred to as "link #a") as a piece of next hop information corresponding to the host Y. The dynamic routing table 3 is stored with link information relating to a line number
10 "f" (which will hereinafter be referred to as "link #f") as a piece of next hop information corresponding to the host Y.

 Further, the static routing table 2 held by the router R2 is stored with link information relating to a line number "b" (which will hereinafter be referred to as [link #b]) as a
15 piece of next hop information corresponding to the host Y. The dynamic routing table 3 is stored with link information relating to a line number "c" (which will hereinafter be referred to as "link #c") as a piece of next hop information corresponding to the host Y.

20 Moreover, the static routing table 2 and the dynamic routing table 3 held by the router R3 are each stored with link information relating to a line number "d" (which will hereinafter be referred to as "link #d") as a piece of next hop information corresponding to the host Y.

25 The static routing table 2 and the dynamic routing table 3 held by the router R5 are each stored with link information relating to a line number "e" (which will hereinafter be

referred to as "link #e") as a piece of next hop information corresponding to the host Y.

When the packet is forwarded from the host X to the host Y, the router R1 receives the packet 6 forwarded from the host X at first. The router R1 judges whether or not the failure occur in the link #a selected by the static routing. The router R1, when judging that no failure occur therein, forwards the packet 6 to the router R2 via the link #a in accordance with the next hop information corresponding to the host Y, which is stored in the static routing table 2.

The router R2, when receiving the packet 6 from the router R1, judges whether or not the failure occur in the link #b selected by the static routing. The router R2, when judging that no failure occur therein, forwards the packet 6 to the router R3 via the link #b in accordance with the next hop information corresponding to the host Y, which is stored in the static routing table 2.

The router R3, when receiving the packet 6 from the router R2, judges whether or not the failure occur in the link #d selected by the static routing. The router R3, when judging that no failure occur therein, forwards the packet 6 to the router R5 via the link #d in accordance with the next hop information corresponding to the host Y, which is stored in the static routing table 2.

The router R5, when receiving the packet 6 from the router R3, judges whether or not the failure occur in the link #e selected by the static routing. The router R5, when judging

that no failure occur therein, forwards the packet 6 to the host Y via the link #e in accordance with the next hop information corresponding to the host Y, which is stored in the static routing table 2.

5 Thus, the each of the routers R1 - R3 and R5, if no failure occur in the link (static route) selected by static routing, forwards the packet 6 to the static route.

FIG. 28 is a diagram showing an example of communications in a case where a failure of a static route occur (cause) in
10 the network system shown in FIG. 27. As shown in FIG. 28, it is assumed that the failure occur in the link #b for the duration of forwarding the packet 6 to the host Y from the host X.

In this case, the router R2 discovers the failure in the link #b, and, when receiving the packet 6 from the router R1,
15 judges that the failure occur in the link #b corresponding to the static route. Then, the router R2 forwards the packet 6 to the router R5 via the link #b in accordance with the next hop information corresponding to the host Y, which is stored in the dynamic routing table 3 (see FIG. 27).

20 The router R5, when receiving the packet 6 from the router R2, judges whether or not the failure occur in the link #e selected by static routing. The router R5, when judging that no failure occur therein, forwards the packet 6 to the host Y via the link #e in accordance with the next hop information
25 corresponding to the host Y, which is stored in the static routing table 2.

FIG. 29 is a diagram showing another example of

communications in the case where the failure occur in the static route in the network system shown in FIG. 27. As shown in FIG. 29, the failure occur in the link #d, and, when the router R3 detects this failure, the router R3 notifies of the failure each
5 of the routers R1, R2 existing anterior to the router R3 itself on the static route from the host X to the host Y.

Thereafter, the router R1 receives the packet 6 addressed to the host Y which has been forwarded from the host X. The router R1 selects the next hop information out of the dynamic
10 routing table 3 (see FIG. 27) on the basis of the failure notification from the router R3. The router R1 forwards the packet 6 to the router R5 via the link #f in accordance with this piece of hop information.

The router R5, when receiving the packet 6 from the router
15 R1, forwards the packet 6 to the host Y via the link #e in accordance with the next hop information corresponding to the host Y, which is stored in the static routing table 2.

Thus, even if the failure occur in the static route (host X → router R1 → link #a → router R2 → link #b → router R3 →
20 link #d → router R5 → link #e → host Y), the packet 6 can be forwarded to the host Y, and the packet reachability can be secured.

Note that as a substitute for the examples explained in FIGS. 28 and 29, each of the routers R1 ~ R5 (the router R5 in
25 the examples in FIGS. 28 and 29), when receiving the packet 6 forwarded via the dynamic route, may forward the packet 6 to the host Y via the link #e in accordance with the next hop

information corresponding to the host Y, which is stored in the dynamic routing table 3. Any one of the existing technologies may be used as a method of detecting the failure in the link #b or the link #d in order for the router R5 to select the dynamic
5 route.

[Second Embodiment]

Next, the communication device in a second embodiment of the present invention will be described. The second embodiment is substantially the same as the first embodiment, except for
10 the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

FIG. 2 is a diagram showing construction of an inputted packet processor 7 provided in the communication device in the
15 second embodiment. The communication device in the second embodiment receives a packet 12. In the inputted packet processor 7, a destination address 12a contained in the packet 12 is inputted, as a common search key, to a static routing table 8 and a dynamic routing table 9 as well.

Then, each of the routing tables 8 and 9 functions to input
20 a piece of next hop information corresponding to the inputted destination address, to the judgement processing unit 4. Excluding the points described above, the construction and functions of the inputted packet processor 7 are the same as
25 those of the inputted packet processor 1.

In the inputted packet processor 7 in the second embodiment, corresponding next hop information is searched from

each of the routing tables 8 and 9 by use of the same information (the same field contained in the packet) contained in a certain field in the packet.

[Third Embodiment]

5 Next, the communication device in a third embodiment of the present invention will be discussed. The third embodiment is substantially the same as the first embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet
10 processor.

As one category of static routing, a method of adding information for actualizing a virtual circuit into IP datagram (IP packet) may be considered other than the method of directly describing the entry in the routing table.

15 The virtual circuit is defined as a technology that has been used in the asynchronous transfer mode (ATM) etc, wherein two points, i.e., a start point and an end point, are connected by the virtual circuit, identification information of a route to the end point is added into the data transferred between those
20 two points, and a node existing on the virtual circuit forwards the data to the route (leading to the end point) based on the identification information.

An approach to an execution of virtual circuit based routing by adding the identification information of the virtual
25 circuit into the IP packet, has been considered over the recent years. According to this approach, the IP packet is transferred through the set virtual circuit, and hence this may be conceived

as one category of static routing. A mpls shim header in MPLS (Multiple Protocol Label Switching) may be one example of the virtual circuit technology.

FIG. 3 is a diagram showing construction of an inputted
5 packet processor 13 provided in the communication device in the third embodiment. The inputted packet processor 13 reflects a policy in the network by static routing that involves the use of the virtual circuit.

Therefore, a packet 18 received (inputted to the inputted
10 packet processor 13) by the communication device in the third embodiment, contains a packet destination address (corresponding to a unique destination address as a second search key) 18a and a virtual circuit number (corresponding to virtual circuit information as a first search key) 18b as pieces
15 of destination information. The first and second search keys may be global and unique destination addresses respectively.

When the packet 18 is inputted to the inputted packet processor 13, the virtual circuit number 18b contained in the packet 18 is inputted to a static routing table 14. The static
20 routing table 14 functions to input, to a judgement processing unit 16, a piece of next hop information (information of the link A) corresponding to the virtual circuit number 18b.

On the other hand, the destination address 18a in the packet 18 is inputted to a dynamic routing table 15. The dynamic
25 routing table 15 functions to input, to the judgement processing unit 16, a piece of next hop information (information of the link B) corresponding to the destination address 18a.

The judgement processing unit 16 receives pieces of next hop information from the dynamic routing table 15 and the static routing table 14 as well. At this time, the judgement processing unit 16, if failure information about the link A is not received, supplies a switch 17 with the next hop information corresponding to the virtual circuit number 18b.

Then, the switch 17 forwards the inputted packet 18 to the link A in accordance with the next hop information received from the judgement processing unit 16. The packet 18 is thereby transmitted on the virtual circuit down to a communication device (host) as the end point.

By contrast, the judgement processing unit 16, if the failure information about the link A is received when receiving the next hop information from the routing tables 14 and 15, inputs the next hop information corresponding to the destination address 18a to the witch 17. The switch 17 forwards the inputted packet 18 to the link B in accordance with the next hop information received from the judgement processing unit 16.

Thus, the inputted packet processor 13, if no failure occur in the link A, reflects the policy in the network by forwarding the packet 18 by use of the virtual circuit.

Whereas if the failure occur in the link A, the inputted packet processor 13 detects the next hop information based on dynamic routing in accordance with the destination address 18b in the packet 18, and forwards the packet 18 to the link (B) corresponding to the detected information. With this operation, as in the first embodiment, even if the failure occur

in the link A, the reachability of the packet 18 can be secured.

[Fourth Embodiment]

Next, the communication device in a fourth embodiment of the present invention will be discussed. The fourth embodiment
5 is substantially the same as the third embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

FIG. 4 is a diagram showing construction of an inputted
10 packet processor 19 provided in the communication device in the fourth embodiment. The inputted packet processor 19 reflects the policy in the network by MPLS-based static routing as one of the virtual circuit technologies.

A packet 24 is received (inputted to the inputted packet
15 processor 19) by the communication device in the fourth embodiment, contains labels 24a, 24b (corresponding to plural pieces of virtual circuit information) used as pieces of route identification information when selecting a route (label switching) in MPLS, and a destination address 24c of the packet
20 24.

The labels 24a, 24b and the destination address 24c are stored in a header of the packet 24 by way of an example. Thus, the protocol related to MPLS permits that the two labels are stored in the header.

25 When the packet 24 is inputted to the inputted packet processor 19, the label 24a stored in a front-side field of the header of the packet 24 is inputted as a first search key to

a static routing table 20. The static routing table 20 functions to input the next hop information (link A) corresponding to the label 24a to a judgement processing unit 22.

5 On the other hand, the destination address 24c in the packet 24 is inputted as a second search key to a dynamic routing table 21. The dynamic routing table 21 functions to input the next hop information (link B) corresponding to the destination address 24c to the judgement processing unit 22.

10 The judgement processing unit 22 receives pieces of next hop information from the dynamic routing table 21 and the static routing table 20 as well. If the failure information about the link A is not received, the judgement processing unit 22 supplies a switch 23 with the next hop information corresponding
15 to the label 24a.

 Then, the switch 23 forwards the inputted packet 24 to the link A in accordance with the next hop information received from the judgement processing unit 22. By contrast, the judgement processing unit 22, if the failure information about
20 the link A is received, inputs the next hop information corresponding to the destination address 24c to the switch 23. The switch 23 forwards the inputted packet 24 to the link B in accordance with the next hop information received from the judgement processing unit 22.

25 Thus, the inputted packet processor 19 in the fourth embodiment, if no failure occur in the link A, reflects the policy in the network by forwarding the packet 24 by MPLS-based

label switching.

Whereas if the failure occur in the link A, the inputted packet processor 19 detects the next hop information based on dynamic routing in accordance with the destination address 24c, and forwards the packet 24 to the link (e.g., link B) corresponding to the detected information. With this operation, as in the third embodiment, even if the failure occur in the link A, the reachability of the packet 24 can be secured, and substantially the same effects as those in the third embodiment can be obtained.

Note that the inputted packet processor 19 is capable of executing the above processes on a packet stored with no label 24b. Further, as a substitute for the mode described above, the label 24b may also be inputted to the static routing table 20.

[Fifth Embodiment]

Next, the communication device in a fifth embodiment of the present invention will be discussed. The fifth embodiment is substantially the same as the fourth embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

The input processing unit 19 in the fourth embodiment, if the failure occur in the link (e.g., link A) selected by static routing, transfers the packet 24 to the link (e.g., link B) selected by dynamic routing.

The transferred packet 24 is off the route (virtual

circuit) based on label switching. If it is assumed herein that the inputted packet processor of the communication device receiving the transferred packet 24 has the same construction as that of the inputted packet processor 24, the label 24a in
5 the packet 24 is inputted to the static routing table 20.

The static routing table 20 does not, however, retain a piece of next hop information corresponding to the label 24a, and is therefore incapable of forwarding the packet 24. Accordingly, when the packet 24 is forwarded to the route (link)
10 selected by dynamic routing, the inputted packet processor, which is to receive the packet 24, must forward the packet 24 to the route selected by dynamic routing. The discussion on the fifth embodiment is an inputted packet processor 25 capable of troubleshooting the above problem.

15 FIG. 5 is a diagram showing construction of the inputted packet processor 25 provided in the communication device in the fifth embodiment. The inputted packet processor 25 includes a static routing table 26, a dynamic routing table 27 and a judgement control unit 28 which correspond to the components
20 of the inputted packet processor 19, and, in addition to these components, further includes a comparing unit 29, an OR circuit 30 and write processing unit (corresponding to a write unit) 33.

The inputted packet processor 25 receives the packet 24
25 explained in the fourth embodiment or a packet 32. The packet 32, unlike the packet 24, has one label 32a and a destination address 32b as the destination information.

The static routing table 26, when the label 32a is inputted, functions to input next hop information corresponding to the label 32a to the judgement processing unit 28 and the comparing unit 29. At this time, the static routing table 26, if a value of the label 32a takes a predetermined special value (corresponding to special data), inputs the inputted special value instead of the next hop information to the judgement processing unit 28 and the comparing unit 29. The special value is set to the predetermined value such as "0" etc.

10 The comparing unit 29 compares the next hop information or the special value inputted from the static routing table 26 with a special value stored in the comparing unit 29 itself. If these two values are coincident with each other (in such a case that the special value is inputted from the static routing
15 table 26), The comparing unit 29 inputs this special value to the OR circuit 30.

The failure information about the link A or a control signal of the operator and the special value given from the comparing unit 29, are inputted to the OR circuit 30. The OR
20 circuit 30, when the failure information or the control signal is inputted, when the special value is inputted, or when both of them are simultaneously inputted, inputs the special value as an output signal to the judgement control unit 28 and the write processing unit 33.

25 When the special value is inputted from the OR circuit 30, the judgement processing unit 28 judges that the failure occur in the link A or the packet 32 (packet 24) is forwarded

off the label switching route, and selects and supplies the next hop information received from the dynamic routing table 27 to the switch 5.

5 The write processing unit 33, to which the packet 32 (packet 24) is inputted, receives the special value from the OR circuit 30. The write processing unit 33, when receiving the special value, rewrites a value of the label 32a of the packet 32 into a special value, and thereafter inputs packet 32 to the switch 32.

10 As a matter of course, however, if the special value has already been written to the label 32a of the inputted packet 32, the process may be not that the write processing unit 33 executes the writing process described above, but that the packet 32 is inputted to the switch 5. The dynamic routing table
15 27 has the same function as what has been described in the fourth embodiment, and hence its explanation is omitted.

 According to the inputted packet processor 25 described above, if the failure occur in the link A selected by static routing, the switch 5 is supplied with the next hop information
20 outputted from the dynamic routing table 27, and the packet of which the label 32a is rewritten into the special value by the write processing unit 33, is inputted to the switch 5. The switch 5 forwards the packet 32 having the special value to the link B.

25 The communication device including an inputted packet processor 25A having the same construction as the inputted packet processor 25 receives the packet 32 having the special

value via the link B, in which case, even if the failure does not occur in a link (e.g., link A1) selected by the static routing table of this inputted packet processor 25A, the judgement processing unit 28 supplies the switch 5 with the next hop information outputted from the dynamic routing table 27. The packet 32 is thereby forwarded from the switch 31 to the link (e.g., link B1) selected by dynamic routing.

Thus, if the packet 32 is forwarded off the label switching route, the label 32a is rewritten into the special value, and the packet 32 having the special value is received by the communication device including the inputted packet processor 25A. Namely, an inbound notification of the special value is given to the communication having the inputted packet processor 25A.

The communication device having the inputted packet processor 25A forwards the packet 32 to the link B selected by dynamic routing. Accordingly, even if the packet 32 is off the label switching route, the reachability of the packet 32 to the end point is secured.

Note that the communication device having the inputted packet processor 25A may be connected to the communication device having the inputted packet processor 19 via the link (B) selected by dynamic routing.

FIG. 30 is a diagram showing an example of the network system to which the communication device in the fifth embodiment is applied, wherein there is given an example of switching to the dynamic route against an occurrence of the failure.

Referring to FIG. 30, the plurality of routers R11 - R15 as the communication devices each including an inputted packet processor 25 are connected to each other via the communication lines, thereby configuring the network. The host X is connected to the router R11, and the host Y is connected to the router R15.

Contents of the static routing table 26 and of the dynamic routing table 27 held in each of the routers R11 - R15 are substantially the same as those shown in FIG. 27, except for such a point that the dynamic routing table 27 of the router R11 retains information on a link #b as a piece of next hop information corresponding to the host Y.

If a failure occur in a link #d for the duration of forwarding the packet 32 from the host X to the host Y, the router R13, when receiving the packet 32 from the router R12, judges that the failure occur in the link #d defined as a static route. Then, a value of the label 32a of the packet 32 is rewritten into a special value, and the packet 32 is transmitted to the router R12 in accordance with the information about the link #b corresponding to the host Y, which is stored in the dynamic routing table 27.

When the router 12 receives the packet 32, because of the value of the label 32a of the packet 32 being the special value, the packet 32 is transmitted via a link #c to the router R15 on the basis of the next hop information corresponding to the host Y that is stored in the dynamic routing table 27. Note that the write processing unit 33 in the router R12 does not

change (through) the special value, or rewrites it into the same special value or into other special value.

The router R15, when receiving the packet 32 from the router R12, based on the special value written in the label 32a,
5 forwards the packet 32 to the host Y via a link #e in accordance with the next hop information corresponding to the host Y that is stored in the dynamic routing table 27.

[Sixth Embodiment]

Next, the communication device in a sixth embodiment of
10 the present invention will be explained. The sixth embodiment is substantially the same as the first embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

15 FIG. 6 is a diagram showing construction of an input processing unit 34 provided in the communication device in the sixth embodiment. The inputted packet processor 34 receives the packet 39 received by the communication device. The packet 39 contains a destination address 39a as a first search key,
20 and a destination address 39b as a second search key.

The destination addresses 39a and 39b have the same data structure, but are global and unique addresses having values different from each other. The destination address 39a is inputted to the static routing table 35, and the destination
25 address 39b is inputted to the dynamic routing table 36.

The configurations and functions of the static routing table 35, the dynamic routing table 36, the judgement processing

unit 37 and the switch 5, are the same as those in the first embodiment, and hence the repetitive explanations are omitted. According to the sixth embodiment, the routing tables 35 and 36 are searched inside by use of pieces of information, (the
5 addresses 39a, 39b) having the same data structure but different from each other, of the packet 39.

[Seventh Embodiment]

Next, the communication device in a seventh embodiment of the present invention will be explained. The seventh
10 embodiment is substantially the same as the second embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

FIG. 7 is a diagram showing construction of an input
15 processing unit 40 provided in the communication device in the seventh embodiment. The inputted packet processor 40 receives an IP packet 45 received by the line interface unit Z. The IP packet 45 is defined as an IP packet (IP datagram) in Version 4, and contains an IPv4 header 45a.

20 FIG. 8 is an explanatory diagram showing a format of the IPv4 header 45a. The IPv4 header 45a contains a destination address 46 of the IP packet 45. This destination address 46 corresponds to the destination address 12a in the second embodiment.

25 The destination address 46 is, when the IP packet 45 is received by the inputted packet processor 40, inputted to a static routing table 41 and a dynamic routing table 42 as a search

key common to these routing tables 41, 42.

Other than the points explained above, the construction and functions in the seventh embodiment are substantially the same as those in the second embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the second embodiment can be obtained in the seventh embodiment.

[Eighth Embodiment]

Next, the communication device in an eighth embodiment of the present invention will be explained. The eighth embodiment is substantially the same as the second embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

FIG.9 is a diagram showing construction of an input processing unit 47 provided in the communication device in the eighth embodiment. The communication device in the eighth embodiment receives an IP packet 52. The IP packet 52 is defined as an IP packet (IP datagram) in Version 6, and contains an IPv6 header 52a.

FIG. 10 is an explanatory diagram showing a format of the IPv6 header 52a. The IPv6 header 52a contains a destination address 53 as a piece of destination information of the IP packet 52. The destination address 53 corresponds to the destination address 12a in the second embodiment.

The destination address 53 is, when the IP packet 52 is received by the inputted packet processor 47, inputted to a

static routing table 48 and a dynamic routing table 49 as a search key common to these routing tables 48, 49.

Other than the points explained above, the construction and functions in the eighth embodiment are substantially the same as those in the second embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the second embodiment can be obtained in the eighth embodiment.

[Ninth Embodiment]

10 Next, the communication device in a ninth embodiment of the present invention will be explained. The ninth embodiment is substantially the same as the third embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet processor.

15 FIG.11 is a diagram showing construction of an input processing unit 54 provided in the communication device in the ninth embodiment. The inputted packet processor 54 reflects the policy in the network by static routing that uses a mpls shim header (hereinafter simply referred to as a "shim" header) in MPLS (Multiple Protocol Label Switching).

20 An IP packet 59 received (inputted to the inputted packet processor 54) by the communication device in the ninth embodiment, contains a shim header 59a and an IPv4 header 45a
25 (see FIG. 8).

FIG. 12 is an explanatory diagram showing a format of the shim header 59a. The shim header is recommended in "MPLS Label

Stack Encoding", draft-ietf-mpls-label-encaps-07.txt" of Internet Draft.

5 The shim header 59a is stored with a label value (corresponding to virtual circuit information) 60 as a piece of destination information, which may be defined as identification information of a label switching route. The label value 60 corresponds to the virtual circuit number 18b in the third embodiment.

10 When the IP packet 59 is received by the inputted packet processor 54, the label value 60 in the shim header 59a of the IP packet 59 is inputted to the static routing table 55. On the other hand, the destination address 46 in the IPv4 header 45a of the IP packet 59 is inputted to the dynamic routing table 56. The destination address 46 corresponds to the destination address 18a in the third embodiment.

15 Other than the points explained above, the construction and functions in the ninth embodiment are substantially the same as those in the third embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the third embodiment can be obtained in the ninth embodiment.

[Tenth Embodiment]

25 Next, the communication device in a tenth embodiment of the present invention will be explained. The tenth embodiment is substantially the same as the fourth embodiment, except for the construction of the inputted packet processor, and therefore the discussion will be focused on the inputted packet

processor.

FIG.13 is a diagram showing construction of an input processing unit 61 provided in the communication device in the tenth embodiment. An inputted packet processor 61 reflects the
5 policy in the network by MPLS-based static routing.

An IP packet 66 is inputted to the inputted packet processor 61. The IP packet 66 contains the shim headers 66a, 66b and the IPv4 header 45a (see FIG. 8). Each of the shim headers 66a, 66b is the same format as the shim header 59a shown
10 in FIG. 12.

The destination address 46 stored in the IPv4 header 45a corresponds to the destination address 24c in the fourth embodiment, and the label value 60 of the shim header 66a corresponds to the label 24a in the fourth embodiment.

15 When the IP packet 66 is received by the inputted packet processor 61, the label value 60 of the shim header 66a stored in a front-side field of the IP packet 66 is inputted to the static routing table 62. On the other hand, the destination address 46 in the IPv4 header 45a of the IP packet 66 is inputted
20 to the dynamic routing table 63.

Other than the points explained above, the construction and functions in the tenth embodiment are substantially the same as those in the fourth embodiment, of which the repetitive explanations are therefore omitted. Substantially the same
25 effects as those in the fourth embodiment can be obtained in the tenth embodiment.

[Eleventh Embodiment]

Next, the communication device in an eleventh embodiment of the present invention will be described. The eleventh embodiment has the points common to the third and ninth embodiments. Therefore, the discussion will be focused on only
5 different points.

FIG. 14 is a diagram showing construction of an inputted packet processor 67 in the eleventh embodiment. The inputted packet processor 67 receives an IP packet 68 containing an IPv6 header 52a in place of the IPv4 header 45a, and executes a routing
10 process. The inputted packet processor 67 differs in terms of this point from the inputted packet processor 54 in the ninth embodiment.

The destination address 53 stored in the IPv6 header 52a stuck to the IP packet 68 corresponds to the destination address
15 18a in the third embodiment. The label value 60 in the shim header 59a of the IP packet 68 corresponds to the virtual circuit number 18b in the third embodiment.

Other configuration and functions of the inputted packet processor 67 are substantially the same as those in the ninth
20 embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the third embodiment can be obtained in the eleventh embodiment.

[Twelfth Embodiment]

Next, the communication device in a twelfth embodiment
25 of the present invention will be described. The twelfth embodiment has the points common to the fourth and tenth embodiments. Therefore, the discussion will be focused on only

different points.

FIG. 15 is a diagram showing construction of an inputted packet processor 69 provided in the communication device in the twelfth embodiment. The inputted packet processor 69 receives an IP packet 70 containing the IPv6 header 52a as a substitute
5 for the IPv4 header 45a, and executes routing. The inputted packet processor 69 differs in terms of this point from the inputted packet processor 61 in the tenth embodiment.

The destination address 53 stored in the IPv6 header 52a
10 stuck to the IP packet 70 corresponds to the destination address 24c in the fourth embodiment, and the label value 60 in a shim header 66a of the IP packet 70 corresponds to the label in the fourth embodiment.

Other configuration and functions of the inputted packet
15 processor 69 are substantially the same as those in the tenth embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the fourth embodiment can be obtained in the twelfth embodiment.

[Thirteenth Embodiment]

20 Next, the communication device in a thirteenth embodiment of the present invention will be described. The thirteenth embodiment has the points common to the third and ninth embodiments. Therefore, the discussion will be focused on different points.

25 FIG. 16 is a diagram showing construction of an inputted packet processor 71 in the thirteenth embodiment. The inputted packet processor 71 reflects the policy in the network by static

routing that uses an ST2 header in Internet Stream Protocol Version 2 (which will hereinafter abbreviated to "ST2" as a virtual circuit.

The communication device in the thirteenth embodiment
5 receives an IP packet 76. The IP packet 76 is inputted to the inputted packet processor 71. An ST2 header 76a and the IPv4 header 45a (see FIG. 8) are stuck to the IP packet 76.

FIG. 17 is an explanatory diagram showing a format of the ST2 header 76a. The ST2 header 76a is stored with a uniqueID
10 77 as a piece of identification information (virtual circuit information) of a route serving as the virtual circuit.

Note that the ST2 header is recommended in "RFC1819 E Aug 95 Internet Stream Protocol Version 2 (ST2) Protocol Specification - Version ST2+".

15 The destination address 46 in the IPv4 header 45a stuck to the IP packet 76 corresponds to the destination address 18a in the third embodiment, and the uniqueID 77 in the ST2 header 76a corresponds to the virtual circuit number 18b in the third embodiment.

20 When the IP packet 76 is inputted to the inputted packet processor 71, the uniqueID 77 in the IP packet 76 is inputted to the static routing table 72. On the other hand, the destination address 46 in the IP packet 76 is inputted to the dynamic routing table 56.

25 Other than the points explained above, the construction and functions in the thirteenth embodiment are substantially the same as those in the ninth embodiment, of which the

repetitive explanations are therefore omitted. Substantially the same effects as those in the third embodiment can be obtained in the thirteenth embodiment.

[Fourteenth Embodiment]

5 Next, the communication device in a fourteenth embodiment of the present invention will be described. The fourteenth embodiment has the points common to the third and thirteenth embodiments. Therefore, the discussion will be focused on different points.

10 FIG. 18 is a diagram showing construction of an inputted packet processor 78 provided in the communication device in the fourteenth embodiment. The inputted packet processor 78 receives an IP packet 9 containing the IPv6 header 52a as a substitute for the IPv4 header 45a, and executes routing. The
15 inputted packet processor 78 differs in this point from the inputted packet processor 71 in the thirteenth embodiment.

 The destination address 53 in the IPv6 header 52a stuck to the IP packet 79 corresponds to the destination address 18a in the third embodiment, and the uniqueID 77 in the ST2 header
20 76a corresponds to the virtual circuit number 18b in the third embodiment.

 Other configuration and functions of the inputted packet processor 78 are substantially the same as those of the inputted packet processor 71 in the third embodiment, of which the
25 repetitive explanations are therefore omitted. Substantially the same effects as those in the third embodiment can be obtained in the fourteenth embodiment.

[Fifteenth Embodiment]

Next, the communication device in a fifteenth embodiment of the present invention will be described. The fifteenth is substantially the same as the sixth embodiment, excluding the construction of the inputted packet processor. Therefore, the discussion will be focused on the inputted packet processor.

FIG. 19 is a diagram showing construction of an inputted packet processor 80 provided in the communication device in the fifteenth embodiment. The inputted packet processor 80 receives an IP packet 85 received by the line interface unit Z.

The IP packet 85 is stuck with two IPv4 headers 85a, 85b. The IPv4 headers 85a, 85b are based on the same format as that of the IPv4 header 45a shown in FIG. 8.

The destination address in the IPv4 header 85a corresponds to the destination address 39a in the sixth embodiment, and the destination address in the IPv4 header 85b corresponds to the destination address 39b in the sixth embodiment.

When the inputted packet processor 80 receives the IP packet 85, the destination address in the IPv4 header 85a stuck to the front-side field of the IP packet 85 is inputted to a static routing table 81. Further, the destination address in the IPv4 header 85b stuck next to the IPv4 header 85a is inputted to a dynamic routing table 82.

Other than the points explained above, the construction and functions in the fifteenth embodiment are substantially the

same as those in the sixth embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the sixth embodiment can be obtained in the fifteenth embodiment.

5 [Sixteenth Embodiment]

Next, the communication device in a sixteenth embodiment of the present invention will be described. The sixteenth embodiment is substantially the same as the sixth embodiment, excluding the construction of the inputted packet processor.

10 Therefore, the discussion will be focused on the inputted packet processor.

FIG. 20 is a diagram showing construction of an inputted packet processor 86 in the sixteenth embodiment.

An IP packet 91 received by the line interface unit Z is
15 inputted to the inputted packet processor 86. The IP packet 91 is stuck with two IPv6 headers 91a, 91b. The IPv6 headers 91a, 91b are based on the same format as that of the IPv6 header 52a (see FIG. 10).

The destination address in the IPv6 header 91a
20 corresponds to the destination address 39a in the sixth embodiment, and the destination address in the IPv6 header 91b corresponds to the destination address 39b in the sixth embodiment.

When the inputted packet processor 86 receives the IP
25 packet 91, the destination address in the IPv6 header 91a stuck to the front-side field of the IP packet 91 is inputted to a static routing table 87. On the other hand, the destination

address in the IPv6 header 91b stuck next to the IPv6 header 91a is inputted to a dynamic routing table 88.

Other than the points explained above, the construction and functions in the sixteenth embodiment are substantially the same as those in the sixth embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the sixth embodiment can be obtained in the sixteenth embodiment.

[Seventeenth Embodiment]

10 Next, the communication device in a seventeenth embodiment of the present invention will be described. The seventeenth embodiment is substantially the same as the sixth embodiment, excluding the construction of the inputted packet processor. Therefore, the discussion will be focused on the
15 inputted packet processor.

FIG. 21 is a diagram showing construction of an inputted packet processor 92 in the seventeenth embodiment.

An IP packet 97 received by the line interface unit Z is inputted to an inputted packet processor 92.

20 The IPv4 header 45a (see FIG. 8) is stuck to the front field of the IP packet 97, and the IPv6 header 52a (see FIG. 10) is stuck next to the IPv4 header 45a.

The destination address 46 in the IPv4 header 45a of the IP packet 97 corresponds to the destination address 39a in the
25 sixth embodiment, and the destination address 53 in the IPv6 header 52a corresponds to the destination address 39b in the sixth embodiment.

When the inputted packet processor 92 receives the IP packet 97, the destination address 46 in the IPv4 header 45a is inputted to a static routing table 93. On the other hand, the destination address 53 in the IPv6 header 52a is inputted to a dynamic routing table 94.

Other than the points explained above, the construction and functions in the seventeenth embodiment are substantially the same as those in the sixth embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the sixth embodiment can be obtained in the seventeenth embodiment.

[Eighteenth Embodiment]

Next, the communication device in an eighteenth embodiment of the present invention will be described. The eighteenth embodiment is substantially the same as the sixth embodiment, excluding the construction of the inputted packet processor. Therefore, the discussion will be focused on the inputted packet processor.

FIG. 22 is a diagram showing construction of an inputted packet processor 98 in the eighteenth embodiment. An IP packet 103 received by the line interface unit Z is inputted to the inputted packet processor 98.

The IPv6 header 52a (see FIG. 10) is stuck to the front field of the IP packet 103, and the IPv4 header 45a (see FIG. 8) is stuck next to the IPv6 header 52a.

The destination address 46 in the IPv4 header 45a of the IP packet 103 corresponds to the destination address 39a in the

sixth embodiment, and the destination address 53 in the IPv6 header 52a corresponds to the destination address 39b in the sixth embodiment.

When the inputted packet processor 98 receives the IP
5 packet 103, the destination address 53 in the IPv6 header 52a is inputted to a static routing table 9, and the destination address 46 in the IPv4 header 45a is inputted to a dynamic routing table 100.

Other than the points explained above, the construction
10 and functions in the eighteenth embodiment are substantially the same as those in the sixth embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the sixth embodiment can be obtained in the eighteenth embodiment.

15 Note that the construction in each of the fifteenth through eighteenth embodiments may be combined with the construction in the fifth embodiment. That is, the inputted packet processor in each of the fifteenth through eighteenth embodiments may be provided with the comparing unit 29, the OR
20 circuit 30 and the write processing unit 33 shown in FIG. 5.

[Nineteenth Embodiment]

Next, the communication device in a nineteenth embodiment of the present invention will be described. The nineteenth embodiment has the points common to the third embodiment, and
25 hence the discussion will be focused on only different points.

FIG. 23 is a diagram showing construction of an inputted packet processor 104 in the nineteenth embodiment. The IP

packet 52 (see FIG. 9) received by the line interface unit Z is inputted to the inputted packet processor 104. The IPv6 header 52a (see FIG. 10) is stuck to the IP packet 52.

When the IP packet 52 is inputted to the inputted packet
5 processor 104, the flow label 53a (see FIG. 10) in the IPv6 header 52a is inputted to a static routing table 105. The flow label 53a is used as a piece of identification information about a route of the virtual circuit, and corresponds to the virtual circuit number (virtual circuit information) 18b in the third
10 embodiment.

The static routing table 105 functions to, when the flow label 53a is inputted thereto, input the next hop information (link A) corresponding to the flow label 53a to a judgement processing unit 107. On the other hand, the destination address
15 53 in the IPv6 header 52a is inputted to a dynamic routing table 106. The destination address 53 corresponds to the address 18a in the third embodiment.

Other than the points explained above, the construction and functions in the nineteenth embodiment are substantially
20 the same as those in the third embodiment, of which the repetitive explanations are therefore omitted. Substantially the same effects as those in the third embodiment can be obtained in the nineteenth embodiment.

[Twentieth Embodiment]

25 Next, the communication device in a twentieth embodiment of the present invention will be described. FIG. 24 is a diagram showing construction of an inputted packet processor 109

provided in the communication device in the twentieth embodiment.

Referring to FIG. 24, the inputted packet processor 109 includes a plurality (n-pieces) of static routing tables 110a ~ 11n (110a, 110b, 110c, ..., 110n), a dynamic routing table 111 and a judgement processing unit 112.

A packet 114 received by the line interface unit Z is inputted to the inputted packet processor 109. The packet 114 contains a piece of destination information thereof. When the inputted packet processor 109 receives the packet 114, the destination information in the packet 114 is inputted to each of the static routing tables 110a ~ 110n and the dynamic routing table 111.

Each of the static routing tables 110a ~ 110n has the same structure as the static routing table 2 in the first embodiment. To be specific, each of the static routing tables 110a ~ 110n is stored with the next hop information corresponding to the destination information. Each of the static routing tables 110a ~ 110n functions to, when the destination information is inputted, input to the judgement processing unit 112 the next hop information corresponding to the inputted destination information. The reason why the plurality (n-pieces) of static routing tables 110a ~ 110n are provided lies in such a scheme that the packet 114, even if a failure occur in the route selected by a certain static routing table, can be forwarded via a route selected by other static routing table. Namely, the static routing tables 110a ~ 110n are provided for attaining multiplex

static routes (redundant configurations). Therefore, the static routing tables 110a - 110n output different pieces of next hop information with respect to a certain piece of destination information.

5 The dynamic routing table 111 has the same structure as the dynamic routing table 3 in the first embodiment. That is, the dynamic routing table 111 retains the next hop information corresponding to the destination information and inputs, when the destination information is inputted, the next hop
10 information corresponding to the inputted destination information to the judgement processing unit 112.

 The judgement processing unit 112 receives the next hop information from the static routing tables 110a - 110n and the dynamic routing table 111. Further, the judgement processing
15 unit 112, as in the first embodiment, receives failure information about plural pieces (n-pieces) of links C (Ca, Cb, ..., Cn) as the routes to be selected by the static routing tables 110a - 110n.

 The judgement processing unit 112, based on the priority
20 given to the pieces of next hop information when selected, selects one piece of next hop information among the plural pieces of next hop information inputted, and inputs the selected next hop information to the switch 5. In this example, the judgement processing unit 112 selects the next hop information
25 given the top priority out of the static routing table 110a. Thereafter, the judgement processing unit 112 selects the next hop information in sequence of the static routing table 110b

(unillustrated), the static routing table 110c (unillustrated), ..., 110n, and finally selects the next hop information from the dynamic routing table 112.

With this processing, the judgement processing unit 112,
5 when receiving the next hop information from the static routing tables 110a - 110n and the dynamic routing table 112, and if receiving the failure information about a route (e.g., the link C1) corresponding to the next hop information from the static routing table 110a, selects the next hop information (the next
10 hop information (link Cb) from the static routing table 110b in this example) corresponding to the next priority, and supplies the selected information to the switch 5.

The judgement processing unit 112, if receiving the failure information about all the links corresponding to the
15 next hop information received from the static routing tables 110a - 110n, selects the next hop information (link B) received from the dynamic routing table 111, and supplies this piece of next hop information to a switch 113.

The switch 5, as in the first embodiment, when the packet
20 114 is inputted, forwards the packet 114 to the link corresponding to the next hop information received from the judgement processing unit 112.

According to the twentieth embodiment, the plurality of static routing tables are provided, and, if the failure occur
25 in the route to be selected by a given static routing table, the packet 114 is forwarded to the route to be selected by other static routing table.

The packet 114 can be thereby forwarded to the route based on static routing even if the failure occur in the route to be selected by a given static routing table, and the policy can be reflected in the network. Then, if the failures occur in
5 all the routes based on static routing, the packet 114 is forwarded to a route based on dynamic routing, whereby the reachability of the packet 114 can be secured as in the first embodiment.

[Twenty First Embodiment]

10 Next, the communication device in a twenty first embodiment of the present invention will be explained. FIG. 25 is a diagram showing construction of an inputted packet processor 115 provided in the communication device in the twenty first embodiment. The inputted packet processor 115 includes
15 a static routing table 116, a dynamic routing table 117, a judgement processing unit 118 and a marking process unit 120.

The inputted packet processor 115 receives a packet 121 received by the line interface unit Z. The packet 121 contains a label 121a and a destination address 121b as pieces of
20 destination information.

When the packet 121 is inputted to the inputted packet processor 115, the label 121a of the packet 121 is inputted to the static routing table 116, and the destination address 121b is inputted to the dynamic routing table 117.

25 Functions of the static routing table 116, the dynamic routing table 117, a judgement processing unit 118 and a switch 119, are substantially the same as those in the inputted packet

processor 19 (see FIG. 4) in the fourth embodiment, and hence their explanations are omitted.

If the failure occur in the link A selected as a next hop by the static routing table 116, a signal (failure information) indicating the failure continues to be inputted to the judgement processing unit 118 and to the marking process unit 120 during a period till that failure is troubleshot.

The judgement processing unit 118, for the duration of the input of the failure information, supplies the switch 5 with the next hop information received from the dynamic routing table 117, thereby selecting a route based on dynamic routing.

The marking process unit 120, after the packet 121 has been inputted, inputs this packet 121 to the switch 5. The marking process unit 120, if no failure information is received, does not execute any processing upon the inputted packet 121 and inputs the packet 121 intact to the switch 5. Namely, the marking process unit 120 simply lets the packet 121 through.

While on the other hand, the marking process unit 120, for the duration of the receipt of the failure information, executes marking with respect to the inputted packet 121 by padding a predetermined mark into a header or user field. Thereafter, the marking process unit 120 inputs the packet 121 to the switch 5. The predetermined mark is, e.g., predetermined bits or a bit string. The packet 121 forwarded from the switch 119 to the route (link B) based on dynamic routing is thereby brought into a state of its having been subjected to marking.

According to the twenty first embodiment, if the failure

occur in the static route, marking is effected on the packet 121 to be forwarded to the dynamic route. The packet 121 having been subjected to marking is available for, e.g., the following purposes.

5 In a case where a network administrator or a service provided using the network provides a user with a service, a fee for providing the service is to be charged on the user in accordance with a packet count of packets used for the user to transmit and receive the data.

10 The network administrator or the service provider is able to provide the user with a proper service by reflecting the policy in the network on the basis of static routing. If the failure occur in the static route, the dynamic route is selected by the inputted packet processor 115, whereby the reachability
15 of the packet 121 is secured.

 If the dynamic route is incapable of reflecting the policy, however, QoS (which is the communication quality) might decline. In this case, the network administrator or the service provider should reduce the service providing fee corresponding to the
20 packet count of the packets forwarded to the dynamic route in consideration of a credibility in the user.

 Then, the inputted packet processor 115 executes marking on the packet 121 to be forwarded to the dynamic route. Therefore, the network administrator or the service provider
25 counts the number of the packets 121 having subjected to marking and reduces the service providing fee corresponding to the counted number of the packets 121, thereby making it feasible

to provide the user with a proper service in terms of the fee. For example, the service providing fee may be discounted by subtracting the number of packets having subjected to marking from the number of charging target packets used by the user.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230